



## Super, versatile and effective graffiti remover for delicate surfaces

### PRODUCT DESCRIPTION

**PureKleen-GR** is a cleaner for the removal of graffiti from painted and non-painted surfaces

Removes graffiti from most surfaces:

- ⇒ Rail Carriages.
- ⇒ Bus Shelters.
- ⇒ Shop Fronts.
- ⇒ Garages;
- ⇒ Tunnel Walls
- ⇒ Test plastic surfaces on a small area to check that there is no effect on the substrate
- ⇒ Can be used on vertical surfaces

### TECHNICAL DATA

- ⇒ Density: 1.10 kg/litre
- ⇒ Freezing point: -4°C
- ⇒ Boiling point: 99°C
- ⇒ Colour: Transparent
- ⇒ Odour: caustic
- ⇒ Fully biodegradable
- ⇒ Fumes in use: None

### PACKAGING

5L, 1 L containers

### CHEMICAL PROPERTIES

Solvent based, activated product

### COVERAGE RATE

Coverage depends on the type of graffiti and porosity of the substrate. The values below are given only as an indication:

2-3 m<sup>2</sup>/Litre

### EQUIPMENT CLEANING

Clean equipment with clean warm water.



Before & after graffiti clean with **PureKleen-GR**

### APPLICATION INSTRUCTIONS

*"Always test apply on a small hidden portion of the substrate. This will ensure the underlying substrate is not affected."*

- ⇒ Apply the product to a dry surface by brush, spray or broom onto the contaminated area.
- ⇒ Leave for the period predetermined in the trial. Agitate with a brush, and remove graffiti with sponges or power washer.
- ⇒ Wash surface with water & clean off any remaining residues
- ⇒ Safe; Easy to use; Fast Acting; Low Fumes.
- ⇒ Versatile

### STORAGE & SHELF LIFE

Store away from frost and heat in a dry place: temperature between 5 °C and 35 °C. Shelf life is 24 months from the production batch date when kept in the original unopened container.

### HEALTH & SAFETY

See Material Safety Data Sheet before use.

### KEEP OUT OF THE REACH OF CHILDREN & ANIMALS

**Important:** The content of this documentation is based on our experience of the product. Rocan Products Ltd guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with Rocan's products or bad weather conditions. For further information, refer to the safety data sheet.

ROCAN PRODUCT CODE: R12

Date of last update: 11.04.18

